



# VX 100 - SAE 10W-30

Superior mineral oil for  
gasoline and diesel engines

## USES

Designed for use in all kinds of daily driving conditions, including roads, motorways, urban traffic, etc.

Provides excellent lubrication and year-round protection for turbocharged and naturally aspirated gasoline and diesel engines.

Compatible with catalytic converters.

### Specifications:

ACEA A3/B4

API SL/CF



## MAIN PHYSICAL DATA

	Methods	Units	10W-30
Density at 20°C	ASTM D4052	kg/m <sup>3</sup>	862
Kinematic viscosity at 40°C	ASTM D445	mm <sup>2</sup> /s	76
Kinematic viscosity at 100°C	ASTM D445	mm <sup>2</sup> /s	12
Viscosity index	ASTM D2270		153
Pour point	ASTM D97	°C	-39
Cleveland Open Cup Flash Point	ASTM D92	°C	216
Dynamic viscosity at -20°C	ASTM D5293	mPa·s	5900
HTHS viscosity (150 °C)	CEC L-036-90	mPa·s	3.6
Sulphated ash	ASTM D874	% mass	1.15
Total Base Number (TBN)	ASTM D2896	mgKOH/g	10

*The data given in this table represents typical production values and should not be taken as specifications.*

## PROPERTIES & ADVANTAGES

- ▶ SAE 10W-30 grade viscosity allows quick oil flow at start-up
- ▶ Excellent detergent/dispersant properties keep engines clean and prevent the formation of deposits.
- ▶ Very good oxidation resistance maintains optimal viscosity over the service life of the oil.
- ▶ Reduces engine wear and helps to improve fuel economy.
- ▶ Good anti-foam and anti-corrosion properties

