



SVX 1000 SNOW 4T - SAE 0W-40

100% synthetic PAO oil for 4-stroke snowmobile engines

USES

100% synthetic PAO lubricant specifically developed for use in modern 4-stroke snowmobile engines. Ultimate protection under freezing temperatures down to -60 C°.

Outstanding engine protection under extreme driving conditions: professional or recreational use, racing, etc., ensuring safe operation of wet clutches.

Suitable for all kinds of gasoline and perfectly compatible with catalytic converters.

Specifications:

API SN

JASO MA2



MAIN PHYSICAL DATA

		Methods	Units	0W-40
Density at	20°C	ASTM D4052	kg/m ³	835
Kinematic viscosity at	40°C	ASTM D445	mm ² /s	81.1
Kinematic viscosity at	100°C	ASTM D445	mm ² /s	14.8
Viscosity index		ASTM D2270		193
Pour point		ASTM D97	°C	-63
Cleveland Open Cup Flash Point		ASTM D92	°C	223
Dynamic viscosity at	-35°C	ASTM D5293	mPa·s	5089
Total Base Number (T.B.N.)		ASTM D2896	mgKOH/g	8.9

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

- ▶ SAE 0W-40 oil grade provides excellent stability at high temperatures and instant lubrication upon start-up.
- ▶ 100% synthetic PAO formula offers optimal protection at high temperatures and reduces oil consumption thanks to its low volatility.
- ▶ Meets JASO MA2 friction test requirements to prevent slipping clutch.
- ▶ Use of specific viscosity index improvers to provide exceptional shear stability. This maintains viscosity in service and enhances the protection of the engine's parts.
- ▶ Good detergent/dispersant properties keep engines clean.



facebook.com/yaccosas

twitter.com/yaccosas

youtube.com

