

# TRANSPRO 15 - SAE 15W-40

Mixed fleet mineral oil for diesel and gasoline engines

#### USES

Suitable for diesel engines, including lorries, construction & agricultural equipment, stationary engines, generators, marine engines,... TRANSPRO 15 – SAE 15W-40 is also suitable for gasoline and diesel engines in mixed fleets of vehicles where the manufacturer recommends the use of **API CI-4/SL or ACEA A3/B4 SAE 15W-40 oil.** Compatible with vehicles fitted with catalytic converters.

## Do not use in vehicles equipped with a Diesel Particulate Filter (DPF) and/or SRC system using AdBlue technology fluid.

#### **Specifications:**

ACEA E7; ACEA A3/B4 API CI-4 / SL MAN M3275 MB 228.3 RENAULT RLD-2 VOLVO VDS-3

#### MAIN PHYSICAL DATA

	Methods	Units	15W-40
Density at 20°C	ASTM D4052	kg/m³	867
Kinematic viscosity at 40°C	ASTM D445	mm²/s	99.9
Kinematic viscosity at 100°C	ASTM D445	mm²/s	14.5
Viscosity index	ASTM D2270		150
Pour point	ASTM D97	°C	-33
Cleveland Open Cup Flash Point	ASTM D92	°C	210
Dynamic viscosity at -20°C	ASTM D5293	mPa⋅s	4044
HTHS viscosity	CEC L-036-90	mPa⋅s	4,13
Sulphated ash	ASTM D874	% mass	1,55
Total Base Number (TBN)	ASTM D2896	mgKOH/g	11.2

The data given in this table represents typical production values and should not be taken as specifications.

### **PROPERTIES & ADVANTAGES**

- Increased protection against wear and corrosion.
- Excellent dispersant-detergent properties for a clean engine.
- ► Specific additives allow the use in a wide range of vehicles and equipment (mixed-fleet)
- ► Multigrade SAE 15W-40 all-season engine oil.
- Excellent resistance to oxidation.













Before using this oil, always check the manufacturer's technical requirements in the vehicle's service manual.