

LUBE S/03 SAE 5W-30

100% synthetic oil for gasoline and diesel engines Reinforced anti-wear technology

USES

100% synthetic oil specifically developed to meet the new STELLANTIS **FPW9.55535/03** specification.

This stringent specification applies to Peugeot, Citroën, DS, Opel and Fiat vehicles equipped with :

-1.2 Pure Tech (EB2 gasoline) 110 and 130 hp engines from 2014 to 2018 (series HNV/HNW/HNX/HNY/HNZ)

- -1.5 BlueHDI (DV5R diesel)
- -2.2 BlueHDI (DW12RU)

LUBE S/03 SAE 5W-30 provides reinforced protection against wear and sludge deposits.

<u>Specifications:</u> ACEA C3, API SN plus; PSA B71 2290; FPW9.55535/03 (Stellantis approved formula)

MAIN PHYSICAL DATA

	Methods	Units	5W-30
Density at 20°C	ASTM D4052	kg/m³	846
Kinematic viscosity at 40°C	ASTM D445	mm²/s	66.4
Kinematic viscosity at 100°C	ASTM D445	mm²/s	11.4
Viscosity index	ASTM D2270		165
Pour point	ASTM D97	°C	-42
Cleveland Open Cup Flash Poin	t ASTM D92	°C	254
HTHS viscosity (150°C)	CEC L-036-90	mPa⋅s	3.5
Sulphated ash	ASTM D874	% mass	0.75
Total Base Number (TBN)	ASTM D2896	mgKOH/g	9.1

The data given in this table represents typical production values and should not be taken as specifications.

PROPERTIES & ADVANTAGES

► Put through specific FPW9.55535/03 series of laboratory tests on DV5 engine quantifying wear and sludge deposits.

► Reinforced anti-wear technology with a viscosity setting at the top of the SAE 30 grade for maximum engine protection (high H.T.H.S. viscosity at 150°C strengthens the lubricating film at high temperature).

- ► Low volatility reduces significantly the oil consumption.
- ► High resistance to LSPI (Low Speed Pre-Ignition).
- ► Longer service life for particulate filter (DPF, GPF).
- "High protection" lubricant allows to maintain optimal engine performance and to extend its lifespan (refer to the OEM maintenance plans)
- ► The use of LUBE S/03 SAE 5W-30 allows to maintain the STELLANTIS manufacturer's warranty.







