



# MULTIP PLUS

Extreme-pressure lithium grease

## USES

Recommended for all parts of a vehicle : ball bearings, loaded bearings, cardan shafts and joints...

This multipurpose extreme-pressure grease is suitable for many different uses, particularly under conditions involving heavy loads and high temperatures.

Wide range of applications: cars, motorcycles, agricultural and construction equipment, industrial vehicles, off-road vehicles...

Effective between -20°C and +120°C (max.140°C).

**Specifications:** NLGI 2 grade  
ISO 6743-9 : ISO-L-XBCHB 2  
DIN 51502 : DIN KP2K-20

## MAIN PHYSICAL DATA

	Grade NLGI 2
Colour	Amber
Kinematic viscosity at 40°C	120 mm <sup>2</sup> /s
Kinematic viscosity at 100°C	11 mm <sup>2</sup> /s
Drop point	> 190°C
Thickener	Lithium
Weld load	315 kg
Water resistance	0-90
Anti-rust performance SKF-EMCOR	Distilled water: 0-0 Salted water : ≤2-2

The data given in this table represents typical production values and should not be taken as specifications.

## PROPERTIES & ADVANTAGES

- ▶ Excellent extreme-pressure properties.
- ▶ Good anti-wear and anti-rust protection.
- ▶ Very good thermal resistance for a lithium-based grease.
- ▶ Good water resistance even in boiling water.
- ▶ Enhanced protection against oxidation.



[facebook.com/yaccosas](https://facebook.com/yaccosas)

[twitter.com/yaccosas](https://twitter.com/yaccosas)

[youtube.com](https://youtube.com)

